



SABINE®

SGM SMP45-T & SGM SMP45-S SHOCKMOUNT PLATE



SGM SMP45-S



SGM SMP45-T

SGM SMP45-S:

1. Unit a two-wire shielded cable and the screw terminal on the bottom of mounting plate by soldering. (The terminal numbers are indicated on the circuit board).
2. For the following procedure, please refer to "SGM SMP45-T mounting / connection" section, step 2 to 6.


MOUNTING / CONNECTIONS:

SGM SMP45-T


1. Connect a two-wire shielded cable to the screw terminal on the bottom of mounting plate (The terminal numbers are indicated on the circuit board)
2. Connect the "shield" to PIN 1, "positive" to PIN 2, "negative" to PIN 3.
3. Make certain of firm connection between the screw terminal and the cable.
4. Position the Shockmount Plate on the mounting surface and fix it with the supplied screw.
5. Secure the connection cable below the mounting surface and reserve a length to guarantee the best isolation.
6. Reassure the firm connection.

DIMENSIONS:

SGM SMP45-T



SGM SMP45-S



FEATURES:

- XLR female type connector
- Soldering-free wiring (SGM SMP45-T)
- Rubber panel isolates the microphone from the mounting surface and provides effective reduction of mechanical noise and vibration.

SPECIFICATIONS:

SGM SMP45-T

Connector: XLR-Female

Dimensions: (mm): 81.9(W), 86(H), 42.7(D)

SGM SMP45-S:

Connector: XLR-Female (lockable)

Dimensions: (mm): 81.9(W), 86(H), 50(D)

